



AdvantEdge R-35 5 5/8" Frame Depth Sliding Door

ADVANTEDGE SERIES SLIDING DOOR

The Quaker AdvantEdge Series Sliding door is ideal for a variety of replacement applications including - Energy Efficient, Apartments, Housing Authority and Assisted Living.

FEATURES

- ◇ **Commercial Framing System**
 - 5 5/8' main frame (4 9/16" fin to interior)
- ◇ **Enhanced Design**
 - Mitered and fusion welded corners
 - 0.075" vinyl thickness
 - Aluminum sill
 - Galvanized steel reinforcements
- ◇ **Glazing**
 - 1" insulated glass
 - Low-E with argon gas
- ◇ **Hardware**
 - Heavy-duty tandem wheel rollers make operation easy and smooth
 - D-Loop Plated Hardware with either thumb latch or keyed locking system
- ◇ **Screen**
 - Extruded aluminum screen frame with BetterVue™ mesh

BENEFITS

- ◇ The capacity to match exterior colors for unique project facades
- ◇ The ability to facilitate custom sizes for taller and wider door openings

OPTIONS

- ◇ **Available Configurations**
 - Fixed-Active
 - Active-Fixed
 - Glide-Fixed-Fixed, Fixed-Glide-Fixed or Fixed-Fixed-Glide
 - Fixed-Active-Active-Fixed
 - Sidelites
 - Transoms
 - Special sizing for ADA purposes
 - Reversible panels only on doors less than 72" tall (some in-field assembly will be required)
- ◇ **Muntin Choices**
 - Internal or simulated divided lites available
- ◇ **Screen**
 - Extruded aluminum screen frame with aluminum wire mesh
 - Extruded aluminum screen frame with sunscreen mesh
 - Extruded aluminum screen frame with stainless steel 0.009" thickness mesh
- ◇ **Glazing**
 - Tilt & Turn blinds between the glass
 - Capillary tubes
 - Wide variety of glazing, tinting and thickness options
- ◇ **Panning & Trim Choices**
 - Wide variety of panning, receptor and trim available
- ◇ **Mulling**
 - Wide variety of structural mulls

PERFORMANCE

- ◇ Structural & Thermal (test reports or thermal simulations available upon request)

Model	AdvantEdge Sliding Door
	Active-Fixed
AAMA/WDMA/CSA 101/I.S.2/A440-08 Rating	R-35
Structural Load P.S.F.	52.5
Air at 25 MPH (cfm/ft ²)	.09
Water (No Penetration) P.S.F.	5.25
U-Value (with EnergyMax Glass Package)	0.24
SHGC (with EnergyMax Glass Package)	0.21
Test size	

Our products are tested to the standards of and certified by the American Architectural Manufacturer's Association, the National Fenestration Rating Council and the Window & Door Manufacturers Association.




VINYL COLORS AND ARCHITECTURAL EXTERIOR PAINT COATINGS AND FINISHES

◇ Solid Vinyl Colors (interior & exterior)



◇ Optional Faux Wood Grain (interior only)



◇ Optional Painted Colors (exterior only)



◇ Optional Unlimited Custom Painted Colors (exterior only)



* Printed colors shown here may not accurately depict actual vinyl or painted colors. Color samples are available upon request.

Our products are tested to the standards of and certified by the American Architectural Manufacturer's Association, the National Fenestration Rating Council and the Window & Door Manufacturers Association.



QUAKER
COMMERCIAL WINDOWS AND DOORS



QUAKER
COMMERCIAL WINDOWS AND DOORS

AdvantEDGE[®]
High-Performance Windows, Doors and Sliding

AdvantEdge
R-35
5 5/8" Frame Depth
Sliding Door

ADVANTEDGE SERIES SLIDING DOOR

Our products are tested to the standards of and certified by the American Architectural Manufacturer's Association, the National Fenestration Rating Council and the Window & Door Manufacturers Association.



QUAKER
COMMERCIAL WINDOWS AND DOORS