



CityVu Windows (C600, C605)



Patented OptiCore® Frame

OptiCore® technology is an architecturally enhanced aluminum frame design that maximizes the thermal, structural and sound performance of each window.




Uncompromised Construction

CityVu Windows with OptiCore® are tested to achieve high performance architectural ratings. OptiCore® technology offers the most advanced thermal barrier system to allow for bigger windows and greater views throughout your home.



Superior Thermal Performance

Along with our energy-efficient glass packages, OptiCore® technology ensures enhanced comfort and energy savings, regardless of region or climate.



Slim Profile, Lightweight Design

CityVu's modern and minimalist aesthetics make for beautiful, modern views.

Contemporary Design With Superior Product Features

CityVu Window (C600, C605) Highlights, Performance and Operation

- Patented OptiCore® Technology Framing System
 - 4-1/8" Architectural Grade Aluminum Frame
 - 4-9/16" and 6-9/16" Jamb Depths
 - Dual Euro-Groove Frame System
- Azo-Core Thermal Barrier System for Increased Energy Efficiency and Reduced Thermal Conductivity
- Multiple Glazing Package Options Compliment Region and Climate
- Structural Mull Availability Offers Wider and Taller Sizing Options
- Square (C600) and Bevel (C605) Stop Options for Enhanced Exterior Look
- Internal or Simulated Divided Light (SDLs) Grids Available
- High-Performance 2604 and 2605 Powder and Class 1 Anodized Finishes
- Optional Exterior and Interior (Two-Tone) Color Finish Options
- Custom Color Matching and Heat Reflective Paint Options
- Easily Removable FlexScreen System

Window Sizing				
Operation	Width		Height	
	Min	Max	Min	Max
Direct Set	15"	144"	15"	144"
Anchor Leg	15"	144"	15"	144"
Casement	24"	48"	22"	96"
Casement Push-Out	18"	48"	24"	72"
Awning	24"	72"	24"	84"

Window Performance						
Operation	Rating	Structural Load (P.S.F.)	Air Infiltration	Water (P.S.F.)	U-Value	SHGC
Direct Set	AW-PG100	100	0.01	12.11	0.15 - 0.29	0.24 - 0.36
Anchor Leg	CW-70	70.18	0.01	12.11	0.24 - 0.29	0.24 - 0.29
Casement	AW-PG70	70.18	0.01	12.11	0.20 - 0.32	0.19 - 0.29
Casement Push-Out	Pending					
Awning	AW-PG70	70.18	0.01	12.11	0.20 - 0.32	0.19 - 0.29

Interior & Exterior Color Options

White	Satin Creme	Sky White II	Oyster White	New Bone White	Polar White	Beige	Sandstone	Toffee	Beige Grey
Earthtone	Teal	Interstate Blue	Patina Green	Holly Green	Moss Green	Redwood	Burgundy	Chestnut	New Dark Bronze
Agate Grey	Slate Grey	Telegrey I	Dark Bronze	Gloss Black	Black	Textured Black	Textured Dark Bronze	Textured Dark Grey	Textured Dark Espresso
Resembles Clear Anodized	Resembles Champagne Light Range	Resembles Champagne Dark Range	Resembles Dark Bronze Light Range	Resembles Dark Bronze Dark Range	Resembles Light Bronze	Resembles Black Anodized	Textured Dark Espresso Heat Reflective	Textured Black Heat Reflective	



Quaker Window Products
504 U.S. Hwy 63 South
Freeburg, MO 65035
(800) 347-0438

www.quakerresidentialwindows.com

Discover More Here:

