



TimberVu W-Series Doors (W200)

The artistic fusing of an architectural aluminum exterior with the classic look and feel of a natural wood interior provides the ageless charm found only in TimberVu W-Series Doors.

Duality by design, the melding of these complimentary materials offer the chance to customize your living space and visually share the timeless comfort seen throughout the broad spectrum of contemporary architectural planning.



Available in Swing or Sliding operational styles along with sidelites, transoms and multiple mulling configurations.

Unique to the market, the SolidCore™ Thermal Barrier System integrates an Azo-Core high-density foam that acts as an insulator against the natural conductivity of heat and cold, allowing for superior energy performance and product integrity regardless of size or operational style.



TimberVu W-Series Swing Door (W200) Highlights, Performance and Operation

- Architectural Grade Aluminum Frame
 - 5-5/8" Frame Depth
 - 4-9/16" and 6-9/16" Jamb Depths
- Thermally Broken Aluminum Frame and OptiCore® Panels
- SolidCore™ Thermal Barrier in Doors
- Corner Key Technology for Maximum Structural Performance
- Available as Inswing (C200I) or Outswing (C200O)
- Adjustable Butt Hinges offer Multi-Directional Adjustment
- Standard, ADA, or No Sill Options
- Butt Joint Panels & Extruded Fin
- Wide and Narrow Panel Options
- Internal or Simulated Divided Light (SDLs) Grids Available
- Pine Interior
- High-Performance 2604 and 2605 Powder and Class 1 Anodized Finishes
- Custom Color Matching and Heat Reflective Paint Options

Swing Door Sizing					
Operation	Width		Height		Max UI
	Min	Max	Min	Max	
Single Panel	24"	43"	78"	120"	180"
Two Panel - French	48"	84"	78"	120"	216"
Sidelight - Narrow	15"	108"	78"	120"	191"
Sidelight - Fixed Panel Set	24"	108"	78"	120"	191"
Transom	12"	120"	12"	108"	191"

Swing Door Performance		
Operation / Style	Structural Rating	U-Value Range
Single Panel	R-50 / LC-50	0.24 - 0.29
Two Panel - French	R-50 / LC-50	0.24 - 0.29
SDL Depth (Max Profile Height)		
Exterior	7/16"	
Interior	9/16"	

TimberVu W-Series Sliding Door (W200) Highlights, Performance and Operation

- Architectural Grade Aluminum Frame
 - 5-5/8" Frame Depth
 - 4-9/16" and 6-9/16" Jamb Depths
- Thermally Broken Aluminum Frame and OptiCore® Panels
- SolidCore™ Thermal Barrier in Doors
- Corner Key Technology for Maximum Structural Performance
- Stainless Steel Quad Precision Bearing Roller System
- Butt Joint Panels & Extruded Fin
- Internal or Simulated Divided Light (SDLs) Grids Available
- Pine Interior
- High-Performance 2604 and 2605 Powder and Class 1 Anodized Finishes
- Custom Color Matching and Heat Reflective Paint Options

Sliding Door Sizing					
Operation	Width		Height		Max UI
	Min	Max	Min	Max	
Two Panel	60"	95"	78"	120"	264"
Four Panel	120"	193"	78"	120"	408"
Sidelight - Narrow	12"	108"	78"	120"	191"
Sidelight - Fixed Panel	24"	108"	78"	120"	191"
Transom	12"	120"	12"	108"	191"

Sliding Door Performance		
Operation / Style	Structural Rating	U-Value Range
Two Panel	R-50 / LC-50	0.26 - 0.31
Four Panel	R-50 / LC-50	0.26 - 0.31
SDL Depth (Max Profile Height)		
Exterior	7/16"	
Interior	9/16"	



Quaker Window Products
 504 U.S. Hwy 63 South
 Freeburg, MO 65035
 (800) 347-0438
www.quakerresidentialwindows.com

Discover More Here :

