









# EdgeVu Windows Size & Performance (H450)

- Patented OptiCore Technology Framing System
  - 3-1/4" Extruded Aluminum Frame
  - 1-1/2" Sightlines Fixed
  - 2-5/16" Sightlines Vent
- Dual Euro-Groove Frame System to Improve Water and Wind Performance
- Sealant Injected Double Corner Key Frame Design Technology Offers Maximum Structural Performance
- Azo-Core Thermal Barrier System for Increased Energy Efficiency and Reduced Thermal Conductivity
- Multiple Glazing Package Options Compliment Region and Climate
- Structural Mull Availability Offers Wider and Taller Sizing Options
- Internal or Simulated Divided Light (SDLs) Grids Available
- High-Performance 2604 and 2605 Powder and Class 1 Anodized Finishes
- Custom Color Matching and Heat Reflective Paint Options

Window Sizing						
Omeration	Wic	ith	Height			
Operation	Min Max		Min	Max		
Awning Roto	20"	72"	18"	84"		
Awning Push Out	20"	72"	18"	84"		
Casement Roto	18"	48"	18"	84"		
Casement Push Out	18"	36"	18"	84"		
Direct Set	10"	120"	10"	120"		
Single Hung	17"	72"	30"	132"		

Window Performance							
Operation	Rating	Structural Load (P.S.F.)	Air Infiltration	Water (P.S.F.)	U-Value	SHGC	
Awning Roto	CW-85	85.2	0.12	15.03	0.31 - 0.35	0.20 - 0.31	
Awning Push Out	CW-90	90.2	0.12	15.03	0.31 - 0.35	0.20 - 0.31	
Casement Roto	CW-90	90.2	0.01	15.03	0.31 - 0.35	0.20 - 0.31	
Casement Push Out	CW-90	90.2	0.11	15.03	0.31 - 0.35	0.20 - 0.31	
Direct Set	AW-100	100.2	0.01	15.03	0.23 - 0.29	0.24 - 0.37	
Single Hung	AW-60	60.15	0.07	10.66	0.29 - 0.33	0.21 - 0.31	

## EdgeVu M-Series Lockbox Doors Size & Performance (M600IL)

- Thermally Broken Aluminum Frame and Door Panels
  - 4-1/2" Frame Depth
  - 2-7/8" Sight Lines
- Azon<sup>™</sup> Polyurethane Thermal Barrier
- Architecturally Correct Dimensional Glass Cut-Out
- Single and 2-Panel French Door Panel Configurations
- Corner Key Frame Technology for Maximum Structural Performance
- Continuous Frame Doors and Transoms
- Architectural Barrel Hinges
- Multipoint Hardware
- Internal or Simulated Divided Light (SDLs) Grids Available
- 1" or 1-3/8" Glazing Pocket
- Offered with Standard, ADA, or No Sill Options
- High-Performance 2604 and 2605 Powder and Class 1 Anodized Finishes
- Custom Color Matching and Heat Reflective Paint Options

Grid Options				
Inswing - Standard				
External Grid Max Height	Internal Grid Max Height			
5/8"	1/2"			

Swing Door Sizing						
	Wi	dth	Height		May III	
Operation	Min	Max	Min	Max	Max UI	
Single Panel	24"	48"	48"	120"	168"	
Two Panel	48"	96"	48"	120"	216"	
Sidelite	15.5"	96"	15.5"	120"	192"	
Transom	15.5"	108"	15.5"	120"	192"	



## EdgeVu M-Series Elongated Lockbox Doors Size & Performance (M600IL)

- Thermally Broken Aluminum Frame and Door Panels
  - 4-1/2" Frame Depth
  - 2-7/8" Sight Lines
- Azon<sup>™</sup> Polyurethane Thermal Barrier
- Architecturally Correct Dimensional Glass Cut-Outs
- True Divided Lights Available in Three or Four lite
- Single and 2-Panel French Door Panel Configurations
- Corner Key Frame Technology for Maximum Structural Performance
- Continuous Frame Doors and Transoms
- Architectural Barrel Hinges
- Multipoint Hardware
- Internal or Simulated Divided Light (SDLs) Grids Available
- 1" or 1-3/8" Glazing Pocket
- Offered with Standard, ADA, or No Sill Options
- High-Performance 2604 and 2605 Powder and Class 1 Anodized Finishes
- Custom Color Matching and Heat Reflective Paint Options

Grid Options				
Inswing - Standard				
External Grid Internal Grid Max Height Max Height				
5/8"	1/2"			

Swing Door Sizing						
0	Wi	Width He		ght	Marrith	
Operation	Min	Max	Min	Max	Max UI	
Single Panel - Three Lite	24"	48"	80"	96"	168"	
Single Panel - Four Lite	24"	48"	96"	120"	168"	
Two Panel - French - Three Lite	48"	96"	80"	96"	216"	
Two Panel - French - Four Lite	48"	96"	96"	120"	216"	
Sidelite	15.5"	96"	15.5"	120"	192"	
Transom	15.5"	108"	15.5"	120"	192"	



## **Glazing Packages Options**

Glazing Package Options							
Glazing Package	U-Value	SHGC	VT	CR			
Energy Enhanced	Lower	Lower	Lower	High			
Energy North	Lower	Moderate	Highest	High			
Energy Basic	Moderate	Low	Higher	Highest			
Energy Plus	Lowest	Low	Higher	Higher			
Energy 3S	Low	Lower	Moderate	Highest			
Energy Max	Lower	Lower	Moderate	Higher			
Energy 4S	Low	Lowest	Moderate	Highest			
Energy 4S+	Lower	Lowest	Moderate	Higher			
Triple Pane	Lowest	Lowest	High	Higher			

- **U-Value:** Represents the heat flow through a window and is measures in BTU/hr-ft². The lower the rating the better the reduction in heat loss.
- **Solar Heat Gain (SHGC):** Is used to measure the amount of radiated heat entering a building. The lower the rating, the better the glazing package is in preventing solar gain.
- Visible Transmittance (VT): Measures the amount of visible light transmitted through a window.
- Condensation Resistance (CR): Measures how well a window resists condensation on its interior surface. The higher the rating, the better the glazing package is able to resist condensation.

## **Comparative Glazing Packages**

Comparative Glazing Packages	STC	OITC		
Single Pane Window	20	19		
1" (25.5 mm) 2-Pane IG Casement	32	28		
1" (25.5 mm) 2-Pane Laminated IG Casement	35	31		
1.375" (34.6 mm) 3-Pane Laminated IG Casement	38	33		
Other Glass Configurations Available Upon Request				

- STC (Sound Transmission Class): is used to calculate the results of soundproofing between rooms or through walls. It is a measurement of decibel reduction. The STC Frequency Scale ranges from 125 Hz to 4000 Hz. The higher the number, the better the product in dampening ambient sound.
- OITC (Outside Inside Transmission Class): This rates the transfer of sound between an outdoor space and an indoor space. OITC has a frequency scale between 80 Hz and 4000 Hz and is used forncalculating sound controls against low frequency exterior sounds. The higher the number, the better the product is in dampening sound.









#### Historic Flair meets Modern Performance

Visually Ageless, the EdgeVu Series brings forward the graded sight lines of steel windows, but adds a Modern Twist and Urban Flair.

Designed to match the iconic look of yesterday and drawn to define the contemporary feel of tomorrow, EdgeVu intertwines modern Technological Advances with a proprietary frame design to provide Superior Performance and Product Flexibility.

Uncompromised Construction, Framed to Perfection.



## A Modern Twist in a Retro Type of Way

Replicating the look and feel of steel, the EdgeVu Series has been Engineered to meet the strictest building codes regardless of region or climate.

Uniquely stylized to Bridge the Patterns of contemporary Architectural Design, Dynamic Features and Simplistic Construction, these characteristics have been Blended together to offer FGIA certified AW-ratings tied to oversized gateway sizes.



A. Azon<sup>TM</sup> Thermal Barrier utilizes a polyurethane foam that has been designed to create greater thermal performance throughout your entire home.

Meets the stringent Energy Star Standards across all 50 states.

B. Euro-Groove Frame and Sash System achieves a tighter perimeter seal and improves, water, air and wind performance characteristics.

C. 1" or 1-3/8" Glazing Pockets offer glass package options to fit every region and every climate.

### Solids, Textures and Metallics

Collaborative color palettes created to define your space and offer a view of who you are.

#### **Natural Tones**

A blending of stepped contrasts and subtle shades.



#### **Monotones**

Illuminating the neutral spectrum of color saturation and hue.



A Color For Every Space: All EdgeVu products can be customized to something truly unique. Whatever your lifestyle and preference, the Quaker Residential color selection has you covered.

#### Metallics

A modern and consistent interpretation of anodized finishes.



Champagne Light Range Anodized



Champagne Dark Range



Light **Bronze** 

Dark Bronze

Light Range

Dark Bronze

Black Dark Range Anodized

**Historic Shades** 

Deepened colors that draw from the classic designs.



#### **Textures**

Mixed to create visual depth and dimension on window and door surfaces.



**Textured Textured Black** Dark Espresso Heat Reflective Espresso Heat Reflective

#### **Hardware Colors and Finishes**

Endearing colors, chosen to enhance and frame our thoughts and visions.

#### EdgeVu Hardware


Available Hardware colors across the EdgeVu Product Line.





Matte Black


Satin Nickel



## EdgeVu Door Configurations


#### LockBox Door

A hinged door that offers a full glass light and a floating keyed lockbox. Available in both Single and 2-Panel French Door Operational Styles.



#### **Elongated LockBox Door**

A hinged door that offers true divided lite glass and a keyed lockbox. Available in both Single and 2-Panel French Door Operational Styles.



## EdgeVu Window Configurations


#### **Picture**

A fixed-pane window that is available in nearly any shape or size.




#### Casement

Swinging outward, this window pivots from the side and is available with Roto-Crank or Outswing Operating hardware.



#### **Awning**

A window that pivots from the top and swings open at the bottom.







Quaker Window Products 504 U.S. Hwy 63 South Freeburg, MO 65035 (800) 347-0438 www.quakerwindows.com





To learn more about Quaker, scan here:

